



P.O. Box 400 | Allendale, SC 29810 | www.fourstarind.com
 Phone: (803) 584-4620 | Fax: (803) 584-4622

Radius and Safe Working Loads

Size	OD	Bend Radius		Safe Working Loads					
		Supported	Unsupported	SDR 9	SDR 11	SDR 13.5	SDR 17	Sch 40	Sch 80
1/2"	0.840	8	11	525	440	365	295	601	768
3/4"	1.050	9	14	821	687	570	460	798	1,040
1"	1.315	12	17	1,288	1,078	894	722	1,340	1,533
1-1/4"	1.660	15	22	2,052	1,717	1,425	1,150	1,604	2,116
1-1/2"	1.900	17	25	2,688	2,249	1,867	1,507	1,919	2,564
2"	2.375	21	32	4,200	3,515	2,917	2,355	2,579	3,545
2-1/2"	2.875	26	38	6,155	5,151	4,274	3,450	4,090	5,409
3"	3.500	32	47	9,122	7,633	6,335	5,114	5,348	7,238
4"	4.500	41	60	15,080	12,618	10,472	8,453	7,618	10,578
5"	5.563	50	75	23,045	19,284	16,004	12,918	10,320	14,669
6"	6.625	60	89	32,684	27,349	22,697	18,321	13,395	20,172
8"	8.625	78	116	55,397	46,355	38,470	31,053	20,158	N/A

- Notes:
- 1) "Safe Working Load" is calculated using the minimum resin tensile of 3000 psi, the average OD and minimum wall thickness, with a 20% safety factor.
 - 2) Supported bend radius is 18 times the OD while unsupported is 27 times the OD.